

4184 E. Conant St., Long Beach, CA 90808 www.RefrigerationX.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Back Bar

Underbar Equipment X-line

Model: XBB-1SB-N6



___ FEATURES & BENEFITS =__

■ Hydrocarbon refrigerants (R-600a)

With innovative and eco-friendly technology, RefrigerationX brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ Forced air cooling system

Fast cooling and balanced temperature throughout the cabinet.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, HCFC free polyurethane insulation.

■ Stainless steel countertop and interior

The exterior of the cabinet is constructed with heavy gauge reinforced stainless steel countertop and wear-resistant black vinyl coated galvanized steel. The interior is painted galvanized steel with reinforced stainless steel floor. RefrigerationX Back Bar model guarantees the utmost in cleanliness and long product life. It also adds a touch of style to the most refined setting.

LED interior lighting

- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 38°F for the best in beverage preservation













Swing 1/2 #of Crated $L \times D^* \times H^{\dagger}$ HP Model Door CU./FT. Barrels Shelves **AMPS** Weight (lbs.) (inches) XBB-1SB-N6 1 7.86 1 2 1/10 2.0 212 235/8 x 293/4 x 341/2

(unit: inch)

Model: XBB-1SB-N6

ELECTRICAL DATA			
Voltage		115/60/1	
Plug Type		(i) NEMA 5-15P	
Full Load Amperes		2.0	
Compressor HP		1/10	
Refrigerant		R-600a	
Cord Length (ft.)		8.5	
Lamp (W)		6.5	
DIMENSIONAL DATA			
Capacity	cu. ft.	7.86	
	1/2 Barrels	1	
	12 oz Cans - 6 pack	33	
	12 oz Bottles - 6 pack	24	
Ext. Length Overall (in.)		235/8 (600mm)	
Ext. Depth Overall (in.)*		293/4 (756mm)	
Ext. Height Overall (in.)†		341/2 (875mm)	
# of Swing Door		1	
# of Shelves		2	
Shelf Size (L x D) (in.)		181/2 x 191/2	
# of Casters		4EA	
Net Weight (lbs.)		190	
Gross Weight (lbs.)		212	

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

† Height does not include 4-7/8" for caster height.

■ WARRANTY: 2 Year Parts and Labor Warranty 5 Year Compressor Warranty


STANDARD FEATURES

- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters with locks on the front set


■ OPTIONAL ACCESSORIES

· Additional PE coated wire shelf: P0178D0100


PLAN VIEW



TOP VIEW



FRONT VIEW



Ver.20250523











Warranty: 800-381-7770 Warranty@RefrigerationX.com

 $^{^{\}star}$ Depth does not include 3/8" for door door handle.