

Refrigeration

We Build Trust, Sell Satisfaction

4184 E. Conant St., Long Beach, CA 90808

www.RefrigerationX.com



Project:

Model #:

Item #:

Available W/H:

Qty:

Approval:

AIA #:

SIS #:

CSI Section 11400

Bottle Cooler

Underbar Equipment
X-line

Model : XBC-50SB-N6



FEATURES & BENEFITS

Hydrocarbon refrigerants (R-600a)

With innovative and eco-friendly technology, RefrigerationX brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Forced air cooling system

Positive guided forced air cooling system chills bottles on top first.

High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

Adjustable, heavy duty, PE (polyethylene) coated dividers

Side mount compressor unit

With compressors positioned on the side of the unit, our refrigerators can now be serviced without being moved. Our innovative, front air intake feature also allows this model to be highly efficient in narrow spaces.

Stainless steel cabinet construction

SB models have an attractive wear-resistant black vinyl exterior. Heavy gauge stainless steel countertop and glide lids are perfect for sanitation and durability. The interior is stainless steel except galvanized steel top. RefrigerationX Bottle Cooler model guarantees the utmost in cleanliness and long product life. It also adds a touch of style to the most refined setting.

Rugged built-in removable bottle cap opener and cap catcher

Large capacity cooler cabinet requires only minimum floor space

Refrigerator holds 33°F ~ 38°F for the best in beverage preservation



Model	Sliding Doors	CU./FT.	Capacity (12oz.btls. - 6 pack)	# of Dividers	HP	AMPS	Crated Weight (lbs.)	L x D* x H† (inches)
XBC-50SB-N6	2	13.5	18	3	1/5	1.8	256	50 x 26 1/2 x 33 1/4

Model : XBC-50SB-N6

ELECTRICAL DATA		
Voltage		115/60/1
Plug Type		 NEMA 5-15P
Full Load Amperes		1.8
Compressor HP		1/5
Refrigerant		R-600a
Cord Length (ft.)		8.5
DIMENSIONAL DATA		
Capacity	12 oz Bottles - 6 pack	18
Net Capacity (cu. ft.)		13.5
Ext. Length Overall (in.)		50 (1270mm)
Ext. Depth Overall (in.)*		261/2 (673mm)
Ext. Height Overall (in.)†		331/4 (844mm)
# of Dividers		3
# of Casters		
Net Weight (lbs.)		234
Gross Weight (lbs.)		256

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 1-7/8" for cap catcher and 1-1/4" for rear spacers.

† Height does not include 3-1/8" for caster height.

■ WARRANTY : 2 Year Parts and Labor Warranty 5 Year Compressor Warranty

■ STANDARD FEATURES


- Anti-corrosion coated evaporator
- Self-contained system
- 2.5" dia. swivel casters with locks on the front set

■ OPTIONAL ACCESSORIES


- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2" caster for underbar series, 1/2" diameter: P0165B0100 (non-brake), P0165B0110 (w/ brake)
- 4" caster, 1/2" diameter & 13 TPI: 30265L0400 (non-brake), 30265L0300 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" - 13 TPI x 1.54": LFM1213566
- 6" adjustable stainless steel leg: P0121P0100

PLAN VIEW


(unit : inch)



TOP VIEW



FRONT VIEW



SIDE VIEW

Ver.20250819



Warranty: 800-381-7770

Warranty@RefrigerationX.com