

4184 E. Conant St., Long Beach, CA 90808 www.RefrigerationX.com

	Project:		
	Model #:		
	Item #:		
	Available W/H:		Qty:
	Approval:		
	AIA #:	SIS #:	
	CSI Section 11400		

Swing Door Merchandisers

____ FEATURES & BENEFITS ____

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, RefrigerationX brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Energy conserving fan control

Utilizing algorithmic air circulation for optimal temperature levels, our innovative fan control system conserves energy by at least 15% and increases compressor life by up to 30%.

Double pane glass doors with Low-E glass

Energy saving double pane glass doors are equipped with Lowemissivity glass, which reduces outer heat gain and decreases energy consumption. It enhances energy efficiency and minimizes condensation. Lightweight door construction also reduces door maintenance and bushing wear, which in turn facilitates smoother door opening.

High-density polyurethane insulation The entire cabinet structure is foamed-in-place using high density, HCFC free polyurethane insulation.

- LED interior lighting
- Adjustable PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 38°F for the best in food preservation



Model : XGM-47W(B)-N



XGM-47B-N

						Refrigerant	Intertek Intertek
Model	Swing Doors	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	${{L} \atop {(inches)}} {L \atop (inches)} {x \atop H}^{\dagger}$
XGM-47W(B)-N	2	40.16	8	1/3	3.7	485	511/8 x 32 x 781/8

* Depth does not include 1-5/8" for door handle. † Height does not include 2-5/8" for caster height.

Swing Door Merchandisers

Model : XGM-47W(B)-N

ELECTRICAL DATA						
Voltage	115/60/1					
Plug Type						
Full Load Amperes	3.7					
Compressor HP	1/3					
Cord Length (ft.)	7					
Refrigerant	R-290					
DIMENSIONAL DATA	IENSIONAL DATA					
# of Doors	2					
Net Capacity (cu. ft.)	40.16 511/8 (1300mm)					
Ext. Length Overall (in.)						
Ext. Depth Overall (in.)*	32 (815mm)					
Ext. Height Overall (in.) [†]	781/8 (1983mm)					
Int. Length Overall (in.)	467/8 (1190mm)					
Int. Depth Overall (in.)	273/8 (695mm)					
Int. Height Overall (in.)	533/4 (1365mm)					
# of Shelves	8					
Shelf Size (L x D) (in.)	221/2 x 231/2					
Bottle Capacity (12oz.)	838					
Net Weight (lbs.)	423					
Gross Weight (lbs.)	485					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 1-5/8" for door handle.

† Height does not include 2-5/8" for caster height.

WARRANTY : ² Year Parts and Labor Warranty 5 Year Compressor Warranty

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Adjustable foot (leg bolt) on the front set
- 2" dia. swivel casters with non-brake on the rear set
- *Two color options available:* white cabinet (W), black cabinet (B).

OPTIONAL ACCESSORIES

- 2" dia. swivel caster (non-brake): X23G3220-010
- Additional PE coated wire shelf: (Left) X47G8360-021 (Right) X47G8360-011

PLAN VIEW

(unit : inch)





FRONT VIEW



Ver.20250519

NATURALI Refrigerant Intertek Warranty: 800-381-7770 Warranty@RefrigerationX.com