

4184 E. Conant St., Long Beach, CA 90808 www.RefrigerationX.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Undercounter Refrigerator

Undercounters X-line

Model: XUR-36-N6



___ FEATURES & BENEFITS =__

■ Hydrocarbon refrigerants (R-600a)

With innovative and eco-friendly technology, RefrigerationX brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlesssly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with themal efficiency.

Cabinet construction

X-line model boasts a stainless steel exterior (door) with AL exterior sides (galvanized steel back and bottom). Interior is stainless steel floor and back with AL sides. It guarantees the utmost in cleanliness and long product life.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Self-contained system
- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- 4" dia. swivel casters with locks on the front set
- Refrigerator holds 33°F ~ 38°F for the best in food preservation



Model	Swing Doors	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H [†] (inches)
XUR-36-N6	2	9.74	2	1/8	1.2	238	363/8 x 30 x 303/8

(unit: inch)

Undercounter Refrigerator

Model: XUR-36-N6

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	NEMA 5-15P			
Full Load Amperes	1.2			
Compressor HP	1/8			
Cord Length (ft.)	9			
Refrigerant	R-600a			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	9.74			
Ext. Length Overall (in.)	363/8 (923mm)			
Ext. Depth Overall (in.)*	30 (762mm)			
Ext. Height Overall (in.)†	303/8 (772mm)			
# of Doors	2			
# of Shelves	2			
Shelf Size (L x D) (in.)	15 x 17			
Net Weight (lbs.)	223			
Gross Weight (lbs.)	238			

Design and specifications subject to change without notice.


Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor


■ OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, ½" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Additional PE coated wire shelf: WM35800100
- Back splash guard: RX-TU-36B
- Double overshelf, stainless steel, 36-3/8" W: RX-TSOS-3R-T

PLAN VIEW



TOP VIEW



Ver.20240327







S YEAR
WARRANTY
(U.S.A only)

ENERGY STAR® Qualified

Warranty: 800-381-7770 Warranty@RefrigerationX.com

^{*} Depth does not include 1-1/4" for rear spacers.

[†] Height does not include 4-3/4" for caster height.